

# Safety Data Sheet

# BOSS® 150 Multi-Seal® Industrial-Cold Storage-Refrigeration-Construction Sealant

## Section 1. Identification

Product Identifier BOSS® 150 Multi-Seal® Industrial-Cold Storage-Refrigeration-Construction

Sealant

Synonyms 15002; 15001

Manufacturer Stock

**Numbers** 

03972WH10; 03972BK10; 03972GY10; C04305WH; C04305BK; C04305GY

Recommended use Refer to Technical Information
Uses advised against Refer to Technical Information

Manufacturer Contact

Address Soudal Accumetric

350 Ring Road

Elizabethtown, KY, 42701

USA

Phone Emergency Phone Fax

(270) 769-3385 (800) 424-9300 (270) 765-2412

CHEMTREC

# Section 2. Hazards Identification

Classification EYE DAMAGE/IRRITATION - Category 2A

HAZARDOUS TO THE AQUATIC ENVIRONMENT - ACUTE HAZARD - Category

3

HAZARDOUS TO THE AQUATIC ENVIRONMENT - LONG-TERM HAZARD -

Category 3

SENSITIZATION - SKIN - Category 1

Signal Word Warning

#### **Pictogram**



Hazard Statements Causes serious eye irritation

Harmful to aquatic life with long lasting effects

Harmful to aquatic life

May cause an allergic skin reaction

**Precautionary Statements** 

Response If eye irritation persists: Get medical advice/attention.

If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. If on skin: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Read label before use.

Wash contaminated clothing before reuse.

Prevention Avoid breathing dust/fume/gas/mist/ vapors/spray.

Avoid release to the environment

Contaminated work clothing must not be allowed out of the workplace.

Wash hands thoroughly after handling. Wear eye protection/face protection.

Wear protective gloves.

Storage N/A

Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Ingredients of unknown

toxicity

0%

Hazards not Otherwise

Classified

None known

## Section 3. Ingredients

CAS	Ingredient Name	Weight %
77-58-7	Dibutyltin dilaurate	0.1% - 1%
1760-24-3	N-beta-(aminoethyl)-gamma-aminopropyltrimethoxysilane	1% - 5%

Occupational exposure limits, if available, are listed in Section 8.

#### Section 4. First-Aid Measures

Comments Treat according to person's condition and specifics of exposure.

Ingestion DO NOT INDUCE VOMITING. Seek immediate medical attention.

Inhalation Remove to fresh air. If symptoms persist, obtain appropriate medical attention.

Skin Contact Remove from skin and immediately flush with water for 15 minutes. Get

medical attention if irritation or ill effects develop or persist.

Immediately flush eyes with water for at least 15 minutes. Get medical Eye Contact

attention if irritation develops.

#### Section 5. Fire Fighting Measures

Suitable Extinguishing On large fires use dry chemical, foam, or water spray. On small fires use Media

carbon dioxide, dry chemical or water spray. Water can be used to cool fire

exposed containers.

Unsuitable Extinguishing

Media

None known

Flammability Limits in Air Not determined Auto-ignition Temperature

Not determined

Special Fire Fighting

**Procedures** 

Fire responders must wear self-contained breathing apparatus and full protective equipment. Move fire-exposed containers if it can be done without risk to firefighters. If possible, control water run-off to prevent environmental

contamination.

Unusual Fire and **Explosion Hazards**  When involved in a fire, this material may decompose and produce the following toxic gases: carbon monoxide, carbon dioxide, nitrogen oxides, aldehydes, silicon dioxide, and various polymer compounds. Contact with

water will release small quantities of flammable methanol.

#### Section 6. Accidental Release Measures

Steps to be taken in case of spill or release

Observe all personal protective equipment recommendations as described in Section 8. Scrape all spilled materials for disposal. This material is not classified as a hazardous waste per 40 CFR 261.

Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable.

# Section 7. Handling and Storage

Handling Avoid breathing vapors in top of shipping container. Keep container closed.

Use with adequate ventilation. Avoid contact with skin and clothing. Wash

throughly after handling.

Storage Keep container closed and store in a cool, well ventilated area, away from

water or moisture.

# Section 8. Exposure Controls/Personal Protection

**ACGIH OSHA STEL** Occupational Exposure Ingredient Name Limits TLV PEL

Dibutyltin dilaurate	N/A	N/A	N/A
N-beta-(aminoethyl)-gamma- aminopropyltrimethoxysilane	N/A	N/A	N/A
animopropylininethoxyshane			

Personal Protective Equipment

N/A

Eye Protection

Use proper protection - safety glasses as a minimum.

Skin Protection Wash at mealtimes and end of shift. If skin contact occurs, change

contaminated clothing as soon as possible and throughly flush affected areas with cool water. Chemical protective gloves are recommended.

Ventilation Respiratory Protection Local exhaust ventilation is recommended to maintain vapor level below TLV.

Use respiratory protection unless adequate exhaust ventilation is provided or exposure assessment demonstrates that exposures are within exposure guidelines. Industrial Hygiene Personnel can assist in judging the adequacy

of existing engineering controls.

Note These precautions are for room temperature handling. Use at elevated

temperatures or aerosol/spray applications may require added precautions.

# Section 9. Physical and Chemical Properties

Physical State	Paste	
Color	Refer to	
	product label	
Odor	Slight	
Odor Threshold	N/A	
Solubility	Water	
	dilutable in	
	wet stage	
Partition coefficient Water/n-octanol	N/A	
VOC%	15 g/L	
Viscosity	N/A	
Specific Gravity	1.63	
Density lbs/Gal	N/A	
Pounds per Cubic Foot	N/A	
Flash Point	200C	
FP Method	N/A	
Ph	N/A	
Melting Point	Not	
	determined	
Boiling Point	Not	
	determined	
Boiling Range	N/A	
LEL	N/A	
UEL	N/A	
Evaporation Rate	Not	
	determined	
Flammability	N/A	
Decomposition Temperature	N/A	
Auto-ignition Temperature	N/A	

Vapor Pressure	Not
	determined
Vapor Density	Not
	determined

Note The above information is not intended for use in preparing product

specifications. Contact Soudal Accumetric before writing specifications.

### Section 10. Stability and Reactivity

**Chemical Stability** Stable

Hazardous polymerization Will not occur

**Products** 

Hazardous Decomposition Thermal breakdown of this product during fire or very high heat conditions may

evolve the following hazardous decomposition products:

Carbon monoxide Carbon dioxide Nitrogen oxides Aldehydes Silicon Dioxide

Various polymer compounds

Materials to Avoid Oxidizing acids, amines, strong caustics, water

Conditions to Avoid Contact with incompatible materials and exposure to extreme temperatures.

### Section 11. Toxicological Information

Carcinogenicity This product is not known to be a carcinogen. **Teratogenicity** This product is not known to be teratogenic. Mutagenicity This product is not known to be a mutagen.

Reproductive Toxin This product is not known to be a reproductive toxin.

# Section 12. Ecological Information

Fate and Effects in Waste

Water Treatment Plants

Complete information is not yet available.

**Environmental Effects** 

Complete information is not yet available.

Environmental Fate and

Complete information is not yet available.

Distribution

## Section 13. Disposal

Waste Disposal Method

We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

# Section 14. Transport Information

UN Number N/A

UN Proper Shipping Name Caulking & GLaziers, NOI

DOT Classification None Packing Group N/A

#### Section 15. Regulatory Information

None

The contents of this MSDS comply with the OSHA Hazard Communication

Standard 29 CFR 1910.1200.

TSCA Status All chemical substances found in this product comply with the Toxic

Substances Control Act inventory reporting requirements.

SARA Title III Section 302

**Extremely Hazardous** 

Substances

SARA Titre III Section 304 None

**CERCLA Substances** 

dangereuses

SARA Title III Section 313

**Toxic Chemicals** 

None present or none present in regulated quantities.

California Proposition 65 This product contains the following chemical(s) listed by the State of California

under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm:

None known

Canada Domestic Substances List All ingredients are listed on the DSL.

#### Section 16. Other Information

Revision Date 10/30/2015

Disclaimer The data contained herein is based upon information that Soudal Accumetric

believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.