

# AFE08C4E-IAA

HFO, R-448A, 60 Hz, 1 -Phase, 115 V

Low Temperature



**Production Status:** Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

## Performance

Evaporator Temp. (°F)	-10	-25
Condensing Temp. (°F)	120	105
Return Gas Temp. (°F)	40	40
Liquid Temp. (°F)	120	105
Capacity (Btu/hr)	771	572
Power (W):	241	188
Current (Amps):	4.20	3.80
EER (Btu/Wh):	3.20	3.05
Mass Flow (lbs/hr):	13	8
<u>Sound Data @</u>		
Sound Power (dBA):	0 Avg	0 Max
Vibration mils(peak-peak):	0.0 Avg	0.0 Max
Record Date:	2016-02-04	

## Mechanical

Displacment(in <sup>3</sup> /Rev):	0.33
Displacment(ft <sup>3</sup> /hr):	40.56
Overall Length (in):	10.50
Overall Width (in):	6.40
Overall Height (in):	7.38
Mounting Length (in):	6.50
Mounting Width (in):	4.00
Mounting Height (in):	7.75 *
Suction Size (in),Type:	5/16 Stub
Discharge Size (in),Type:	1/4 Stub
Initial Oil Charge (oz):	12
Oil Recharge (oz):	10
Net Weight (lbs):	22.0
Internal Free Volume (in <sup>3</sup> ):	
Horse Power:	
*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

## Electrical

LRA-High*(Amp):	26.5
LRA Low* (Amp):	
LRA-Half Winding (Amp):	
MCC (Amps):	5.5
Max Operating Current(Amp):	
RLA, MCC/1.4;use for contactor selection (Amp):	3.9
RLA, MCC/1.56;use for breaker & wire size selection (Amp):	3.5
RPM:	
UL File No:	
UL File Date:	
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.	

## Capacitors

Type	Part No	Low MFD	High MFD	Volts	User Description
Start Capacitor	014-0053-18	145.0	175.0	165	

## Alternate Applications

Refrigerant	Voltage	Phase	Freq (Hz)	Application
R-404A HFC	115	1	60	Extended Medium Temp, A-Line
R-449A HFO	115	1	60	Low Temperature