

AFE13C4E-IAA

HFO, R-448A, 60 Hz, 1 -Phase, 115 V

Low Temperature



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evaporator Temp. (°F)	-10	-25
Condensing Temp. (°F)	120	105
Return Gas Temp. (°F)	40	40
Liquid Temp. (°F)	120	105
Capacity (Btu/hr)	1190	883
Power (W):	367	286
Current (Amps):	5.35	4.85
EER (Btu/Wh):	3.25	3.10
Mass Flow (lbs/hr):	19	13
<u>Sound Data @</u>		
Sound Power (dBA):	0 Avg	0 Max
Vibration mils(peak-peak):	0.0 Avg	0.0 Max
Record Date:	2017-02-21	

Electrical

LRA-High*(Amp):	37.5
LRA Low* (Amp):	
LRA-Half Winding (Amp):	
MCC (Amps):	7.8
Max Operating Current(Amp):	
RLA, MCC/1.4;use for contactor selection (Amp):	5.6
RLA, MCC/1.56;use for breaker & wire size selection (Amp):	5.0
RPM:	
UL File No:	
UL File Date:	
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.	

Mechanical

Displacment(in^3/Rev):	0.54
Displacment(ft^3/hr):	65.21
Overall Length (in):	10.50
Overall Width (in):	6.40
Overall Height (in):	7.88
Mounting Length (in):	6.50
Mounting Width (in):	4.00
Mounting Height (in):	8.25 *
Suction Size (in),Type:	5/16 Stub
Discharge Size (in),Type:	1/4 Stub
Initial Oil Charge (oz):	12
Oil Recharge (oz):	10
Net Weight (lbs):	28.0
Internal Free Volume (in^3):	
Horse Power:	
*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Capacitors

Type	Part No	Low MFD	High MFD	Volts	User Description
Start Capacitor	014-0053-35	189.0	227.0	165	

Alternate Applications

Refrigerant	Voltage	Phase	Freq (Hz)	Application
R-404A HFC	115	1	60	Extended Medium Temp, A-Line
R-449A HFO	115	1	60	Low Temperature