

ITEM # CAPF3743D6, CAPF - CASED PAINTED UPFLOW/DOWNFLOW

The Daikin brand All-aluminum CAPF Cased Upflow/Downflow Indoor Coils are made for split system air conditioners and heat pumps. This unit features aluminum tubing and corrugated aluminum fin coils and rust resistant, high-temperature, thermoplastic drain pans. The CAPF cabinet is painted nickel gray.

- Check flowrate for cooling and heat pump applications
- Rifled aluminum tubing and corrugated aluminum fin coil
- All-aluminum evaporator coil
- Galvanized, leather grain-embossed finish
- Rust-

[+ more](#)



[Specifications](#) | [Features](#)

Specifications

| | |
|---------------------------|------------------------------|
| UPC Code | 663051540989 |
| Nominal Capacity | 42000 Btu/h 3 to 3 1/2 TR |
| Width | 24 1/2 in |
| Opening Width | 23.5 in |
| Depth | 21 in |
| Height | 30 in |
| Suction Connection Height | 25 in |
| Liquid Connection | 3/8 in |

| | |
|--------------------|---------|
| Suction Connection | 7/8 in |
| Piston Size | .078 in |
| Weight | 75 lb |

Features

Standard Features

- All-Aluminum evaporator coil
- Optimized for use with R-410A refrigerant
- Some models suitable for use with R-410A or R-22 refrigerant
- CAPT models feature factory-installed thermal expansion valves for cooling and heat pump applications
- Check flowrator for cooling and heat pump applications
- Vertical and horizontal models available
- 21" depth for easier attic access
- Split seam front for easy access
- Foil-faced insulation covers the internal casing to reduce cabinet condensation
- Galvanized, leather grain-embossed finish
- Rust resistant, thermoplastic drain pans featuring a low water-retention design
- DecaBDE-free thermoplastic drain panwith secondary drain connections
- UV-resistant drain pan
- AHRI certified; ETL listed