

CR47KQE-PFV

HCFC, R-22, 60 Hz, 1 -Phase, 208/230 V

Air Conditioning



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evaporator Temp. (°F)	45	45
Condensing Temp. (°F)	130	100
Return Gas Temp. (°F)	65	65
Liquid Temp. (°F)	115	85
Capacity (Btu/hr)	41800	55000
Power (W):	3990	3430
Current (Amps):	19.00	16.70
EER (Btu/Wh):	10.50	16.10
Mass Flow (lbs/hr):	610	685
<u>Sound Data @</u>		
Sound Power (dBA):	78 Avg	83 Max
Vibration mils(peak-peak):	4.0 Avg	5.0 Max
Record Date:	2018-08-21	

Mechanical

Displacment(in ³ /Rev):	4.95
Displacment(ft ³ /hr):	602.06
Overall Length (in):	10.38
Overall Width (in):	9.09
Overall Height (in):	14.81
Mounting Length (in):	7.50
Mounting Width (in):	7.50
Mounting Height (in):	15.19 *
Suction Size (in),Type:	7/8 Stub
Discharge Size (in),Type:	1/2 Stub
Initial Oil Charge (oz):	45
Oil Recharge (oz):	43
Net Weight (lbs):	77.0
Internal Free Volume (in ³):	
Horse Power:	
*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Electrical

LRA-High*(Amp):	132.0
LRA Low* (Amp):	
LRA-Half Winding (Amp):	
MCC (Amps):	34.5
Max Operating Current(Amp):	
RLA, MCC/1.4;use for contactor selection (Amp):	24.6
RLA, MCC/1.56;use for breaker & wire size selection (Amp):	22.1
RPM:	
UL File No:	
UL File Date:	
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.	

Capacitors

Type	Part No	Low MFD	High MFD	Volts	User Description
Start Capacitor	014-0006-13	189.0	227.0	330	HIGH TORQUE
Start Capacitor	014-0061-13	64.0	77.0	330	LOW TORQUE
Run Capacitor	014-0064-15	45.0	0.0	440	

Alternate Applications

Refrigerant	Voltage	Phase	Freq (Hz)	Application
R-407C HFC	208/230	1	60	Air Conditioning
R-407C HFC	200	1	50	Air Conditioning