## CS14K6E-TF5

HFC, R-404A, 60Hz, 3- Phase, 200/230 V **Extended Medium Temp** 

## **Production Status:**

Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Pe	erformance			Me	chanical
Evap(°F)/Cond(°F)	20 / 120	-10 / 120	Number of Cylinders:	2	Displ(in^3/Rev):
			Bore Size(in):	1.52	Displ(ft^3/hr):
RG(°F)/Liq(°F)	40.0 / 120.0	40.0 / 120.0	Stroke(in):	0.80	
Capacity	13900	5370			
(Btu/hr) Power (Watts):	2200	1370	Overall Length (in):	10.23	Mounting Length (in):
Current (Amps):	6.70	4.30	Overall Width (in):	9.65	Mounting Width (in):
EER (Btu/Wh):	6.30	3.90	Overall Height (in):	13.44	Mounting Height (in):
Mass Flow (lbs/hr):	331	122			
			Suction Size (in):		5/8 Stub
Sound Power (dBA):	0 Avg	0 Max	Discharge Size (in):		1/2 Stub
Vibration (mils(peak-peak)):	0.0 Avg	0.0 Max	Oil Recharge (oz):		43
			Initial Oil Charge (oz):	:	45
Record Date:	2002-05-02		Net Weight (lbs):		61
			Internal Free Volume	(in^3):	
			Horse Power:		
			*Overall compressor I mounting grommets.	neight on	Copeland Brand Product's

			Jui		
LRA-High*:	55.0	MCC (Amps):	12.8	UL File No:	
LRA-Half Winding:		RPM:	3500	UL File Date:	28-Dec-1984
LRA Low*:		Max Operating Current:	10.6		
RLA(=MCC/1.4;use for contactor s	selection):	9.1			
RLA(=MCC/1.56;use for breaker &	& wire size se	lection): 8.2			
*Low and High refer to the low and	d high nomina	al voltage ranges for which the	motor is approve	d.	
	LRA-Half Winding: LRA Low*: RLA(=MCC/1.4;use for contactor RLA(=MCC/1.56;use for breaker &	LRA-Half Winding: LRA Low*: RLA(=MCC/1.4;use for contactor selection): RLA(=MCC/1.56;use for breaker & wire size se	LRA-High*: 55.0 MCC (Amps):   LRA-Half Winding: RPM:   LRA Low*: Max Operating Current:   RLA(=MCC/1.4;use for contactor selection): 9.1   RLA(=MCC/1.56;use for breaker & wire size selection): 8.2	LRA-Half Winding:RPM:3500LRA Low*:Max Operating Current:10.6RLA(=MCC/1.4;use for contactor selection):9.1RLA(=MCC/1.56;use for breaker & wire size selection):8.2	LRA-High*:55.0MCC (Amps):12.8UL File No:LRA-Half Winding:RPM:3500UL File Date:LRA Low*:Max Operating Current:10.6RLA(=MCC/1.4;use for contactor selection):9.1

Alternate Applications					
Refrigerant	Freq (Hz)	Phase	Voltage	Application	
R-22 HCFC	60	3	200/230	Medium Temperature	
R-134a HFC	60	3	200/230	High Temp	
R-404A HFC	60	3	200/230	High Temp	
R-507 HFC	60	3	200/230	Extended Medium Temp	
R-507 HFC	60	3	200/230		
R-134a HFC	50	3	200/240	High Temp	
R-404A HFC	50	3	200/240	Extended Medium Temp	
R-404A HFC	50	3	200/240		
R-507 HFC	50	3	200/240	Extended Medium Temp	
R-507 HFC	50	3	200/240		



Alternate Applications						
Refrigerant	Freq (Hz)	Phase	Voltage	Application		
R-507 HFC	50	3	200/240	Medium Temperature		