ITEM # CTXG18QVJUS, EMURA - CTXG SERIES - INDOOR UNIT



Specifications | Dimensions | Features | Benefits

Specifications -				
	Cooling Capacity	18000 Btu/h		
	Heating Capacity	18000 Btu/h		
	Front Panel Color	Silver		
	Heat Insulation	Both Liquid and Gas Pipes		
	Airflow Rate (H) - Cooling	364 ft³/min 10.3 m³/min		
	Airflow Rate (H) - Heating	438 ft³/min 12.4 m³/min		
	Airflow Rate (M) - Cooling	286 ft³/min 8.1 m³/min		
	Airflow Rate (M) - Heating	350 ft³/min 9.9 m³/min		
	Airflow Rate (L) - Cooling	233 ft³/min 6.6 m³/min		
	Airflow Rate (L) - Heating	265 ft³/min 7.5 m³/min		
	Airflow Rate (SL) - Cooling	219 ft³/min 6.2 m³/min		
	Airflow Rate (SL) - Heating	212 ft³/min 6 m³/min		

Fan Type	Cross Flow Fan
Fan Speed	5 Steps, Quiet, Auto
Air Direction Control	Right, Left, Horizontal, Downward
Air Filter	Removable, Washable, Mildew Proof
Running Current (Rated) - Cooling	0.14 A
Running Current (Rated) - Heating	0.21 A
Power Consumption Rated - Cooling	28 W
Power Consumption Rated - Heating	42 W
Power Factor - Cooling	87.0 to 96.1 %
Power Factor - Heating	87.0 to 96.1 %
Sound Pressure Level (H) - Cooling	46 dBA
Sound Pressure Level (H) - Heating	47 dBA
Sound Pressure Level (M) - Cooling	40 dBA
Sound Pressure Level (M) - Heating	41 dBA
Sound Pressure Level (L) - Cooling	35 dBA
Sound Pressure Level (L) - Heating	35 dBA
Sound Pressure Level (SL) - Cooling	32 dBA
Sound Pressure Level (SL) - Heating	32 dBA
Temperature Control	Microcomputer Control
Frequency	60 Hz
Voltage	208 to 230 V
Weight	12 kg 27 lb
Gross Weight	16 kg 36 lb

Depth	8-3/8 in 303 mm
Width	39-5/16 in 998 mm
Height	11-15/16 in 212 mm
Packaged Depth	15-5/16 in 389 mm
Packaged Width	43-3/8 in 1101 mm
Packaged Height	12-11/16 in 322 mm
Pipe Connections - Liquid	1/4 in 6.4 mm
Pipe Connections - Gas	1/2 in 12.7 mm
Pipe Connections - Drain	11/16 in 18 mm

Features

Matches with MXS, RMXS & MXL multi-port models only

Designer looks

Intelligent Eye to detect when room has been unoccupied, and automatically changes to an energy-saving operation.

Compatible with optional wireless interface adapter for Wi-Fi control with Daikin Comfort Control App Titanium Apatite Photocatalytic Air Purifying Filter

Benefits

12 Year limited parts warranty with online registration5 Year limited parts warranty for commercial applicationsHigh efficiency cooling and heating operation provides utility bill savings

12/30/2020 | Page 4 of 4