

# MODEL NUMBER FTKN09NMVJU, 0.75-TON WALL MOUNTED UNIT COOLING ONLY



[Specifications](#) | [Dimensions](#) | [System Efficiency Metrics](#) | [Features](#) | [Benefits](#)

## Specifications

Model Type	Wall Mounted Unit
Frequency	60 Hz
Power Supply	208-230 V/ 60 Hz / 1 Phase
Voltage	208-230 V
Current	0.23 - 0.21 A
Number of Speeds	5
Cooling Capacity	9000 Btu/h
Moisture Removal	0.32 gal/h
Power Consumption (Rated)	25 - 25 W
Power Factor (Rated)	52.3-51.8 %
Fan Type	Cross Flow Fan
Fan Motor Output	18 W
Fan Speed	5 Steps, Quiet, Auto
Air Direction Control	Right, Left, Horizontal and Downward
Temperature Control	Microcomputer Control
Air Filter	Removable / Washable / Mildew Proof
Heat Insulation	Both Liquid and Gas Pipes

Operation Sound (H/M/L) - Cooling	43 / 35 / 27 / 19 dBA
Airflow Rate (H)	403 ft <sup>3</sup> /min 11.4 m <sup>3</sup> /min
Airflow Rate (M)	286 ft <sup>3</sup> /min 8.1 m <sup>3</sup> /min
Airflow Rate (L)	219 ft <sup>3</sup> /min 6.2 m <sup>3</sup> /min
Airflow Rate (SL)	145 ft <sup>3</sup> /min 4.1 m <sup>3</sup> /min
Sensible Capacity	8010 Btu/h
Max/Min Cooling Capacity	10200/4400 Btu/h
Rated Cooling Conditions	Ambient (°F DB/WB): 95 / 75 Indoor (°F DB/WB): 80 / 67
Chargeless	32-13/16 ft 10 m
Amount of Additional Charge of Refrigerant	0.21 oz/ft 20 g/m
Weight	18 lb 8 kg
Gross Weight	24 lb 11 kg

## Dimensions

Depth	8-3/4 in 223 mm
Width	30-5/16 in 770 mm
Height	11-1/4 in 285 mm
Pipe Connections - Liquid	1/4 in 6.4 mm
Pipe Connections - Gas	3/8 in 9.5 mm

	9.5 mm
Pipe Connections - Drain	5/8 in 16.0 mm
Max. Interunit Height Difference	39-3/8 ft 12 m
Max. Interunit Piping Length	49-1/4 ft 15 m
Packaged Depth	14-3/16 in 360 mm
Packaged Width	32-11/16 in 831 mm
Packaged Height	12 in 305 mm

## System Efficiency Metrics

System Performance SEER	15.0
-------------------------	------

## Features

- 15 SEER / Up to 12.2 EER
- Mold-resistant washable air filter
- Inverter driven swing compressor
- Specialized drain pan design for improved cold climate drainage
- Vertical auto-swing air flow
- Hot-start function to eliminate start-up drafts
- Powerful (turbo) and Econo mode settings
- Wireless remote included

## Benefits

- 10 Year limited parts warranty with online registration
- 5 Year limited parts warranty for commercial applications
- Low profile indoor unit with matte white finish
- Compatible with optional Daikin ENVi Wi-Fi capable Smart Control

