

# RRT10K1E-PFV

HFC, R-134a, 60 Hz, 1 -Phase, 208/230 V

High Temp



**Production Status:** Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

## Performance

Evaporator Temp. (°F)	45	20
Condensing Temp. (°F)	130	120
Return Gas Temp. (°F)	65	65
Liquid Temp. (°F)	130	120
Capacity (Btu/hr)	10250	6570
Power (W):	1260	992
Current (Amps):	6.15	5.20
EER (Btu/Wh):	8.15	6.60
Mass Flow (lbs/hr):	179	105
<u>Sound Data @</u>		
Sound Power (dBA):	0 Avg	0 Max
Vibration mils(peak-peak):	0.0 Avg	0.0 Max
Record Date:	2011-04-18	

## Electrical

LRA-High*(Amp):	46.0
LRA Low* (Amp):	
LRA-Half Winding (Amp):	
MCC (Amps):	11.2
Max Operating Current(Amp):	
RLA, MCC/1.4;use for contactor selection (Amp):	8.0
RLA, MCC/1.56;use for breaker & wire size selection (Amp):	7.2
RPM:	
UL File No:	SA-2337
UL File Date:	2009-02-05
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.	

## Mechanical

Displacement(in <sup>3</sup> /Rev):	1.70
Displacement(ft <sup>3</sup> /hr):	206.38
Overall Length (in):	10.30
Overall Width (in):	6.93
Overall Height (in):	9.84
Mounting Length (in):	8.00
Mounting Width (in):	4.80
Mounting Height (in):	10.43 *
Suction Size (in),Type:	1/2 Stub
Discharge Size (in),Type:	3/8 Stub
Initial Oil Charge (oz):	22
Oil Recharge (oz):	20
Net Weight (lbs):	39.0
Internal Free Volume (in <sup>3</sup> ):	
Horse Power:	
*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

## Capacitors

Type	Part No	Low MFD	High MFD	Volts	User Description
Start Capacitor	014-0061-29	108.0	130.0	330	
Run Capacitor	014-0064-11	25.0	0.0	440	

## Alternate Applications

Refrigerant	Voltage	Phase	Freq (Hz)	Application
R-450A HFO	208/230	1	60	High Temp
R-513A HFO	208/230	1	60	High Temp