

RST64C1E-IAV

HFO, R-448A, 60 Hz, 1 -Phase, 208/230 V

Medium Temperature



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evaporator Temp. (°F)	20	0
Condensing Temp. (°F)	120	110
Return Gas Temp. (°F)	40	40
Liquid Temp. (°F)	120	110
Capacity (Btu/hr)	6320	4150
Power (W):	1315	989
Current (Amps):	8.35	7.35
EER (Btu/Wh):	4.80	4.20
Mass Flow (lbs/hr):	106	63
<u>Sound Data @</u>		
Sound Power (dBA):	0 Avg	0 Max
Vibration mils(peak-peak):	0.0 Avg	0.0 Max
Record Date:	2016-02-15	

Electrical

LRA-High*(Amp):	43.0
LRA Low* (Amp):	
LRA-Half Winding (Amp):	
MCC (Amps):	12.6
Max Operating Current(Amp):	
RLA, MCC/1.4;use for contactor selection (Amp):	9.0
RLA, MCC/1.56;use for breaker & wire size selection (Amp):	8.1
RPM:	
UL File No:	
UL File Date:	
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.	

Mechanical

Displacement(in ³ /Rev):	1.37
Displacement(ft ³ /hr):	166.14
Overall Length (in):	10.30
Overall Width (in):	7.10
Overall Height (in):	9.20
Mounting Length (in):	8.00
Mounting Width (in):	4.80
Mounting Height (in):	9.90 *
Suction Size (in),Type:	3/8 Stub
Discharge Size (in),Type:	1/4 Stub
Initial Oil Charge (oz):	15
Oil Recharge (oz):	13
Net Weight (lbs):	39.0
Internal Free Volume (in ³):	
Horse Power:	
*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Capacitors

Type	Part No	Low MFD	High MFD	Volts	User Description
Start Capacitor	014-0061-27	88.0	106.0	330	

Alternate Applications

Refrigerant	Voltage	Phase	Freq (Hz)	Application
R-404A HFC	208/230	1	60	Extended Medium Temp
R-449A HFO	208/230	1	60	Medium Temperature