

ZF11K4E-TF5

HCFC, R-22, 60 Hz, 3 -Phase, 200/230 V
 Low Temp, Liquid Injected



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evaporator Temp. (°F)	-25	-40
Condensing Temp. (°F)	105	105
Return Gas Temp. (°F)	65	65
Liquid Temp. (°F)	105	105
Capacity (Btu/hr)	10900	7390
Power (W):	2320	2180
Current (Amps):	8.00	7.70
EER (Btu/Wh):	4.70	3.40
Mass Flow (lbs/hr):	145	98
<u>Sound Data @</u>		
Sound Power (dBA):	76 Avg	81 Max
Vibration mils(peak-peak):	2.0 Avg	3.0 Max
Record Date:	2004-07-27	

Mechanical

Displacment(in ³ /Rev):	3.49
Displacment(ft ³ /hr):	424.13
Overall Length (in):	9.57
Overall Width (in):	9.52
Overall Height (in):	16.46
Mounting Length (in):	7.50
Mounting Width (in):	7.50
Mounting Height (in):	16.69 *
Suction Size (in),Type:	3/4 Stub
Discharge Size (in),Type:	1/2 Stub
Initial Oil Charge (oz):	49
Oil Recharge (oz):	45
Net Weight (lbs):	64.0
Internal Free Volume (in ³):	251.0
Horse Power:	3.50

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

Electrical

LRA-High*(Amp):	88.0
LRA Low* (Amp):	
LRA-Half Winding (Amp):	
MCC (Amps):	17.5
Max Operating Current(Amp):	14.5
RLA, MCC/1.4;use for contactor selection (Amp):	12.5
RLA, MCC/1.56;use for breaker & wire size selection (Amp):	11.2
RPM:	3500
UL File No:	SA-2337
UL File Date:	1995-02-28

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Capacitors

Alternate Applications

Refrigerant	Voltage	Phase	Freq (Hz)	Application
R-134a HFC	200/230	3	60	Medium Temp, Liquid Injected
R-134a HFC	200/230	3	60	Low Temp, Liquid Injected
R-134a HFC	200/220	3	50	Medium Temp, Liquid Injected
R-134a HFC	200/220	3	50	Low Temp, Liquid Injected
R-404A HFC	200/230	3	60	Medium Temp, Liquid Injected
R-404A HFC	200/230	3	60	Low Temp, Low Condensing
R-404A HFC	200/220	3	50	Medium Temp, Liquid Injected
R-404A HFC	200/220	3	50	Low Temp, Liquid Injected
R-404A HFC	200/230	3	60	Low Temp, Liquid Injected
R-404A HFC	200/220	3	50	Low Temp, Low Condensing

Alternate Applications

<u>Refrigerant</u>	<u>Voltage</u>	<u>Phase</u>	<u>Freq (Hz)</u>	<u>Application</u>
R-507 HFC	200/230	3	60	Medium Temp, Liquid Injected
R-507 HFC	200/230	3	60	Low Temp, Liquid Injected
R-507 HFC	200/220	3	50	Medium Temp, Liquid Injected
R-507 HFC	200/220	3	50	Low Temp, Low Condensing
R-507 HFC	200/220	3	50	Low Temp, Liquid Injected
R-22 HCFC	200/230	3	60	Medium Temp, Liquid Injected
R-22 HCFC	200/220	3	50	Medium Temp, Liquid Injected
R-22 HCFC	200/220	3	50	Low Temp, Liquid Injected
R-407C HFC	200/230	3	60	UL Medium Temp
R-407C HFC	200/230	3	60	Low Temp, Liquid Injected
R-407C HFC	200/220	3	50	UL Medium Temp
R-407C HFC	200/220	3	50	UL Low Temp
R-407C HFC	200/230	3	60	UL Low Temp
R-407A HFC	200/220	3	50	UL Medium Temp
R-407A HFC	200/220	3	50	UL Low Temp
R-407A HFC	200/230	3	60	UL Low Temp
R-407A HFC	200/220	3	50	Low Temp, Liquid Injected
R-407A HFC	200/230	3	60	Low Temp, Liquid Injected
R-407F HFC	200/220	3	50	Low Temp, Liquid Injected
R-407F HFC	200/230	3	60	Low Temp, Liquid Injected
R-448A HFO	200/220	3	50	Medium Temp, Liquid Injected
R-448A HFO	200/220	3	50	Low Temp, Liquid Injected
R-448A HFO	200/230	3	60	Medium Temp, Low Condensing
R-448A HFO	200/230	3	60	Low Temp, Liquid Injected
R-448A HFO	200/230	3	60	Medium Temp, Liquid Injected
R-449A HFO	200/220	3	50	Medium Temp, Liquid Injected
R-449A HFO	200/220	3	50	Low Temp, Liquid Injected
R-449A HFO	200/230	3	60	Medium Temp, Liquid Injected
R-449A HFO	200/230	3	60	Low Temp, Liquid Injected