

ZF33K4E-TWD

Replacement: ZF34K5E-TFD



HCFC, R-22, 60 Hz, 3 -Phase, 460 V
Low Temp, Liquid Injected

Production Status: This compressor and/or application of this compressor is not available to U.S. OEM customers. A field replacement is currently available through a U.S. Emerson Climate Technologies Wholesaler. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evaporator Temp. (°F)	-25	-40
Condensing Temp. (°F)	105	105
Return Gas Temp. (°F)	65	65
Liquid Temp. (°F)	105	105
Capacity (Btu/hr)	31100	21800
Power (W):	6800	6100
Current (Amps):	12.20	11.50
EER (Btu/Wh):	4.60	3.60
Mass Flow (lbs/hr):	414	290
<u>Sound Data @</u>		
Sound Power (dBA):	86 Avg	91 Max
Vibration mils(peak-peak):	2.0 Avg	3.0 Max
Record Date:	2004-07-22	

Mechanical

Displacment(in ³ /Rev):	10.10
Displacment(ft ³ /hr):	1226.83
Overall Length (in):	12.44
Overall Width (in):	14.50
Overall Height (in):	21.34
Mounting Length (in):	8.65
Mounting Width (in):	8.65
Mounting Height (in):	22.09 *
Suction Size (in),Type:	1 3/4 Rotolo
Discharge Size (in),Type:	1 1/4 Rotolo
Initial Oil Charge (oz):	140
Oil Recharge (oz):	137
Net Weight (lbs):	221.0
Internal Free Volume (in ³):	1037.0
Horse Power:	10.00

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

Electrical

LRA-High*(Amp):	127.0
LRA Low* (Amp):	
LRA-Half Winding (Amp):	
MCC (Amps):	20.5
Max Operating Current(Amp):	22.3
RLA, MCC/1.4;use for contactor selection (Amp):	14.6
RLA, MCC/1.56;use for breaker & wire size selection (Amp):	13.1
RPM:	3500
UL File No:	SA-9747
UL File Date:	1900-01-01

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Capacitors

Alternate Applications

Refrigerant	Voltage	Phase	Freq (Hz)	Application
R-134a HFC	460	3	60	High Temp
R-134a HFC	460	3	60	Medium Temp, Liquid Injected
R-134a HFC	460	3	60	Low Temp, Liquid Injected
R-134a HFC	380/420	3	50	High Temp
R-134a HFC	380/420	3	50	Medium Temp, Liquid Injected
R-134a HFC	380/420	3	50	Low Temp, Liquid Injected
R-404A HFC	460	3	60	Medium Temp, Liquid Injected
R-404A HFC	460	3	60	Low Temp, Low Condensing
R-404A HFC	380/420	3	50	Medium Temp, Liquid Injected
R-404A HFC	380/420	3	50	Low Temp, Liquid Injected

Alternate Applications

<u>Refrigerant</u>	<u>Voltage</u>	<u>Phase</u>	<u>Freq (Hz)</u>	<u>Application</u>
R-404A HFC	380/420	3	50	Low Temp, Low Condensing
R-404A HFC	460	3	60	Low Temp, Liquid Injected
R-507 HFC	460	3	60	Medium Temp, Liquid Injected
R-507 HFC	460	3	60	Low Temp, Liquid Injected
R-507 HFC	380/420	3	50	Medium Temp, Liquid Injected
R-507 HFC	380/420	3	50	Low Temp, Low Condensing
R-507 HFC	380/420	3	50	Low Temp, Liquid Injected
R-22 HCFC	460	3	60	Medium Temp, Liquid Injected
R-22 HCFC	380/420	3	50	Medium Temp, Liquid Injected
R-22 HCFC	380/420	3	50	Low Temp, Liquid Injected