

ZR72KCE-TFD

HCFC, R-22, 60 Hz, 3 -Phase, 460 V

Air Conditioning



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evaporator Temp. (°F)	45	45
Condensing Temp. (°F)	130	100
Return Gas Temp. (°F)	65	65
Liquid Temp. (°F)	115	85
Capacity (Btu/hr)	73500	86000
Power (W):	6250	4460
Current (Amps):	9.10	7.10
EER (Btu/Wh):	11.70	19.30
Mass Flow (lbs/hr):	1080	1110
<u>Sound Data @</u>		
Sound Power (dBA):	75 Avg	80 Max
Vibration mils(peak-peak):	2.0 Avg	3.0 Max
Record Date:	2014-03-06	

Mechanical

Displacement(in ³ /Rev):	5.98
Displacement(ft ³ /hr):	727.10
Overall Length (in):	9.69
Overall Width (in):	9.69
Overall Height (in):	17.75
Mounting Length (in):	7.50
Mounting Width (in):	7.50
Mounting Height (in):	18.00 *
Suction Size (in),Type:	7/8 Stub
Discharge Size (in),Type:	1/2 Stub
Initial Oil Charge (oz):	60
Oil Recharge (oz):	56
Net Weight (lbs):	85.0
Internal Free Volume (in ³):	248.0
Horse Power:	6.00

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

Electrical

LRA-High*(Amp):	75.0
LRA Low* (Amp):	
LRA-Half Winding (Amp):	
MCC (Amps):	14.0
Max Operating Current(Amp):	12.1
RLA, MCC/1.4;use for contactor selection (Amp):	10.0
RLA, MCC/1.56;use for breaker & wire size selection (Amp):	9.0
RPM:	3500
UL File No:	SA-2337
UL File Date:	1993-07-26

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Capacitors

Alternate Applications

<u>Refrigerant</u>	<u>Voltage</u>	<u>Phase</u>	<u>Freq (Hz)</u>	<u>Application</u>
R-134a HFC	460	3	60	Air Conditioning
R-134a HFC	380/420	3	50	Air Conditioning
R-22 HCFC	380/420	3	50	Air Conditioning
R-407C HFC	460	3	60	Air Conditioning
R-407C HFC	380/420	3	50	Air Conditioning